

#### **HEAD OFFICE**

17 Tapgeol-gil Ungchon-myeon Ulju-gun Ulsan Korea Tel.82-52-228-7500 Fax.82-52-268-5578

OVERSEAS DIRECT

Tel.82-52-228-7563 SEOUL OFFICE

Fax.82-52-228-7530

Fax.82-2-2635-1382 Tel.82-2-2635-1380

KUKIL INNTOT is a professional manufacturer of gasket, packing coupling with the latest technology not only for the plant but also the plant maintenance and emergency repair

# **ISOLATION KIT** HIFLEX-HIFS

#### **Product Reference:**

K/# HIFLEX-HIFS

## **Description:**

KUKIL HIFLEX-HIFS is a product with the special insulation coating on the front of a metal core, and has the excellent restoration rate by inserting a spring inside. It can be applied to a higher temperature comparing with the conventional epoxy-based insulating gasket, and has the excellent insulation and sealing performance at high temperature due to the special insulation coating.

#### Service:

Maximum recommended Temperature : 260 ℃ Maximum recommended Pressure: 100 bar

#### Construction:

Insulating Gasket

Insulating Sleeve

Insulating Metal Washer

Insulating film







- Insulating Material SS316L + Special insulation coating
- Insulating Material
- GRE NEMA G-10 - GRE NEMA G-11
- Insulating Material
- Carbon Steel with Zinc Coating + Insulation film
- Carbon Steel with Zinc Coating + Mica

# **Typical Physical Properties:**

| Standard        | Test Method           | Unit  | Result                |
|-----------------|-----------------------|-------|-----------------------|
| ASTM D257       | Insulation Resistance | MΩ    | 3.6 x 10 <sup>5</sup> |
| KS M ISO 2409   | Cross-cut             | Grade | 1                     |
| KS M ISO 1518-1 | Scratch Resistance    | -     | No defects            |

### Gasket Design Data:

| Gasket Factor " m " | Min. Design Sealing Stress " y " |  |
|---------------------|----------------------------------|--|
| 3.75                | 7,600 psi                        |  |

# **Availability:**

Gasket Size(OD): Max 1,200mm (Special sizes can be manufactured when you order)

Thickness: 5mm

#### Remark:

- MESC 85/300 Shell TAT Certification.
- The specification of product is written by manufacturer, and it is changed frequently.
- Non-seam work is available only for those whose out-diameter is 1200mm or below.