



KUKIL INNTOT CO., LTD.

HEAD OFFICE
17 Tappeol-gil Ungchon-myeon Uiju-gun Ulsan Korea
Tel.82-52-228-7500 Fax.82-52-268-5578
OVERSEAS DIRECT
Tel.82-52-228-7563 Fax.82-52-228-7530
SEOUL OFFICE
Tel.82-2-2635-1380 Fax.82-2-2635-1382

VOC PACKING TYPE " FV101V "

KUKIL INNTOT is a professional manufacturer of gasket, packing coupling with the latest technology not only for the plant but also the plant maintenance and emergency repair.

Product Reference :

K/# VOC-FV101V

Description :

VOC-FV101V is manufactured with the same Cup & Cone structure as VOC-HP21, so it has an even surface pressure when installed, so it can have excellent sealing performance even at low clamping pressure. The upper and lower parts are composed of Graflex braid packing with Inconel Wire inserted and the middle part is composed of Graflex Die Molded Rings. By inserting Inconel Wire into Graflex, it can be used at high temperature and high pressure, and corrosion of steam can be suppressed through surface corrosion treatment.

Service :

Maximum recommended Temperature : -240 ~ 450°C (Non-Oxidation)
-240 ~ 650°C (Oxidation)

Maximum recommended Pressure : Class 150LB ~ 2500LB

Construction :



Applications :

Steam & Water.
Gases & LNG.
Hydrocarbon & Oil.
Heat medium.
Organic solvents.
Volatile organic compounds.
Extremely low temperature fluids.
etc.

Availability :

Gasket Size : Order based
Thickness : Order based

Remark :

- The specification of product is written by manufacturer, and it is changed frequently.