

HEAD OFFICE

17 Tapgeol-gil Ungchon-myeon Ulju-gun Ulsan Korea Tel.82-52-228-7500 Fax.82-52-268-5578

OVERSEAS DIRECT

Tel.82-52-228-7563 Fax.82-52-228-7530 **SEOUL OFFICE**

Tel.82-2-2635-1380 Fax.82-2-2635-1382

KUKIL INNTOT is a professional manufacturer of gasket, packing coupling with the latest technology not only for the plant but also the plant maintenance and emergency repair.

RUBBER SHEET GASKET

Type ' KR 1 '

Product Reference:

K/# KR1

Description:

KR 1, made of natural rubber, is the main component isoprene, and This material has excellent elasticity, mechanical properties, abrasion resistance.

However, since oil resistance, heat resistance, weather resistance, ozone resistance, etc. are not good, so we recommended to use other types of rubber gasket in these environments.

Service:

Maximum recommended Temperature : -50 ~ 70°C

Maximum Pressure: 10 Kg_f/cm²

Applications

Water, Alcohol.

Organic Acids, Ketones. Aldehydes, Brake oil, etc.

Construction:



NR Rubber (Natural Rubber)

Gasket Design Data : standard ASME Section™ Div.1

shore hardness	Gasket Factor " m "	Min. Design Sealing Stress " y "
Below 75A	0.5	0 psi
Higher 75A	1.0	200 psi

Availability:

Gasket Size: Max. Ø1200 Thickness: 1.5mm, 3.0mm, etc.

Remark:

• The specification of product is written by manufacturer, and it is changed frequently.