

HEAD OFFICE

17 Tapgeol-gil Ungchon-myeon Ulju-gun Ulsan Korea Tel.82-52-228-7500 Fax.82-52-268-5578

OVERSEAS DIRECT

Tel.82-2-2635-1380

Tel.82-52-228-7563 Fax.82-52-228-7530 **SEOUL OFFICE**

Fax.82-2-2635-1382

KUKIL INNTOT is a professional manufacturer of gasket, packing coupling with the latest technology not only for the plant but also the plant maintenance and emergency repair.

IX-SEAL RING

Product Reference:

IX-SEAL RING

Description:

IX-SEAL RING is a sealing product used in NORSOK Compact flange connections. It is manufactured according to NORSOK standard L-005 and can be made of various materia Is such as stainless steel and carbon steel. In addition, PTFE coating is applied to the s urface to identify the material.

Service:

Maximum recommended Temperature : -101 ~ 250 $^{\circ}\mathrm{C}$ Maximum recommended Pressure : Class 150LB ~ 2500LB

Construction:



Gasket Design Data:

PTFE Coating

IX-Seal Ring Material	Flange Material	Temperature	Color
Carbon steel CD360LT or low alloy steel, e.g. AISI 4140	Carbon steel	-50℃~250℃	Blue
22Cr Duplx	Stainless steel	-50℃~250℃	Yellow
17/4PH	Stainless steel	-50℃~250℃	Orange
Nickel alloys such as alloy 625 or similar	Stainless steel	-101℃~250℃	Black

Gasket Seating Surface Finish

AARH (µm)	Classification	
Max. 0.8	Sealing faces	
Max. 6.3	All other surfaces	

Availability:

Gasket Size: Standard

Remark:

• The specification of product is written by manufacturer, and it is changed frequently.